GC 5000 GAS COMPRESSOR









EQUIPMENT FEATURES

- Recovery speeds from 1-5 lb per minute (depending on solvent)
- · Integrated NEMA7 Switch for ease of installation and operation
- $\cdot \;\;$ Built to last durable construction and reliable operation
- · Certified for use in Class 1, Division 1 environments
- · Oil-less piston and PTFE seals
- · Designed for minimal maintenance
- UL listed



The **GC 5000** is **compliant in all regulated jurisdictions*** & engineer peer reviewed

EQUIPMENT SPECIFICATIONS	
Dimensions (approx.)	41" L x 33" W x 50" D
Weight	496 lb
Shipping Weight	545 lb
Volts	240V
Amps	11A
Hertz	60 hZ
Compressor	Oil-Less Piston, PTFE Seals
Displacement	Min rpm - CFM (m3/hr) 3.58 (6.1) Max rpm - CFM (m3/hr) 8.44 (14.3)
MAWP	350 psia (2,413 kPa)
Max. Discharge Temp.	350°F (176°C)
Inlet/Outlet Size	3/4" (can be reduced)
Warranty	Two-Years (Parts & Labor)

COMPLIANCE

- · UL & CSA compliant
- · Class 1, Division 1, Group D compliant
- · Class II, Groups F&G compliant

INTEGRATED NEMA7 SWITCH

Easy Installation & Operation





LICENSED ELECTRICIAN INSTALL IS REQUIRED

